

## VAMC WACO, TEXAS

## SECTION 09 30 13 - CERAMIC/PORCELAIN TILING

## PART 1 - GENERAL

## 1.1 DESCRIPTION

This section specifies ceramic and quarry tile, (water resistant backing board for wall tile specified in Section 09 29 00). Tile colors as selected by Project Manager/Contracting Officers Technical Representative (PM/COTR) .

## 1.2 RELATED WORK

- A. Sealing of joints where specified: Section 07 92 00, JOINT SEALANTS.
- B. ~~Color,~~ texture and pattern of field tile and trim shapes, size of field tile, trim shapes, ~~and color of grout specified: SCHEDULE FOR FINISHES,~~ and Refer to the Drawings and as specified herein.
- C. Metal and resilient edge strips at joints with new resilient flooring, and carpeting: Section 096519, RESILIENT TILE FLOORING, and Section 096800, CARPETING.

## 1.3 SUBMITTALS

- A. Submit in accordance with Section 01 33 23, SHOP DRAWINGS, PRODUCT DATA, AND SAMPLES.
- B. Samples:
  - 1. Base tile, each type, each color, each size.
  - 2. Floor tile panels, 225 mm by 225 mm (9 inches by 9 inches), each type, color, size and pattern.
  - 3. Quarry tile, each type, color, and size.
  - 4. Wall (or wainscot) tile, each color, size and pattern.
  - 5. Trim shapes, bullnose cap and cove including bullnose cap and base pieces at internal and external corners of vertical surfaces, each type, color, and size.
- C. Product Data:
  - 1. Tile, marked to show each type, size, and shape required.
  - 2. Dry-set Portland cement mortar and grout
  - 3. Divider strip; 4. Reinforcing tape; 5. Leveling compound.
  - 6. Organic adhesive; and 7. Chemical resistant mortar and grout (Epoxy).
- D. Certification:
  - 1. Master grade, ANSI A137.1.
  - 2. Manufacturer's certificates indicating that the following materials comply with specification requirements: